




US



### General Specifications

- Input: 100~240Vac/ 50~60Hz
- Output: +5VDC/0~2000mA Regulated
- DC Cord: 5 FT, 20 AWG
- Operating/Storage Temperature: 0°C ~+40°C/ -10°C~+55°C
- Operating/Storage Humidity: 5%~90%RH
- Approvals: UL/CUL/FCC/LPS/BSMI/PSE/CCC/RCM/PSB/KC/IRAM/TUV-GS,BS/CE/WEEE/ROHS/VI
- Meets Energy Efficiency Level VI Standards
- Protection: Over Voltage/Short Circuit
- Packaged Unit Weight: .26 lb
- Carton Quantity: 80 pcs

### Inner Box Dimensions



100 x 70 x 46mm

<b>ITEM NO.</b>	S-5V0-2A0-U30-MINB	<b>PART TITLE</b>	Energy Efficient 5 VDC / 2A North American Input Power Supply
<b>PART NO.</b>	S6-052A0P-US-MINIB	 <b>CONDOR ELECTRONICS, INC.</b> T: 408-745-7141 F: 408-745-0439 990 San Antonio Road Palo Alto, CA 94303 USA <a href="mailto:sales@condorelectronics.net">sales@condorelectronics.net</a>	
<b>DATE</b>	07.06.2016		
<b>APPROVAL</b>	TN		
<b>UNIT</b>	mm		
<b>REV</b>	0		