


General Specifications

- Input: 100~240Vac/ 50~60Hz
- Output: +5VDC/0~2000mA Regulated
- Operating/Storage Temperature: 0°C ~+40°C/ -20°C~+80°C
- Operating/Storage Humidity: 5%~90%RH
- Approvals: UL/CUL/FCC/LPS/BSMI/PSE/CCC/RCM/PSB/KC/IRAM/TUV-GS,BS/CE/WEEE/ROHS/VI
- Meets Energy Efficiency Level VI Standards
- Protection: Over Voltage/Short Circuit
- Packaged Unit Weight: .38 lb
- Carton Quantity: 50 pcs


WHITE INNER BOX DIMENSIONS

FULL SET


INDIVIDUAL INTERCHANGEABLE PLUG



100 x 55 x 87mm



80 x 65 x 45mm

ITEM NO.	S-5V0-2A0-P30	PART TITLE	Energy Efficient 5 VDC / 2A Universal Input Power Supply with USB
PART NO.	S6-052A0P	 CONDOR ELECTRONICS, INC. T: 408-745-7141 F: 408-745-0439 780 Montague Expy. Ste. 406 San Jose, CA 95131 USA sales@condorelectronics.net	
DATE	4.25.2016		
APPROVAL	TN		
UNIT	mm		
REV	0		