



Output Plug and Polarity are Dependent on Customer Requirements

### General Specifications

- Input: 100~240Vac/ 47~63Hz
- Output: +20VDC/0~2000mA Regulated
- DC Cord: 5FT, 18AWG
- Operating/Storage Temperature: 0°C ~+40°C/ -20°C~+60°C
- Operating/Storage Humidity: 20%~80%RH/10%~90%RH
- M.T.B.F.: 50,000 Hrs. Minimum (25°C Ambient Temp., Full Load)
- Approvals: UL/CUL/FCC/LPS/PSE/ BSMI /TUV/ CE/WEEE/ROHS/VI
- Meets Energy Efficiency Level VI Standards
- Protection: Over Voltage/Short Circuit/Over Current
- Packaged Unit Weight: .50 lbs
- Box Quantity: 40 pcs

White Inner Box Dimensions

<i>ITEM NO.</i>	S-20V0-2A0-IDG30	<i>PART TITLE</i>	Energy Efficient 20 VDC / 2.0A Universal Input Power Supply
<i>PART NO.</i>	S6-202A0I	 <b>CONDOR ELECTRONICS, INC.</b> T: 408-745-7141 F: 408-745-0439 990 San Antonio Road Palo Alto, CA 94303 USA <a href="mailto:sales@condorelectronics.net">sales@condorelectronics.net</a>	
<i>DATE</i>	1.9.2017		
<i>APPROVAL</i>	WS		
<i>UNIT</i>	mm		
<i>REV</i>	0		