


Output Plug and Polarity are Dependent on Customer Requirements

General Specifications

- Input: 100~240Vac/ 47~63Hz
- Output: +48VDC/0~500mA Regulated
- DC Cord: 5 FT, 22 AWG
- Operating/Storage Temperature: 0°C ~+40°C/ -20°C~+80°C
- Operating/Storage Humidity: 20%~80%RH/ 10%~90%RH
- Approvals: UL/CUL/FCC/LPS/BSMI/WEEE/ROHS/VI
- Meets Energy Efficiency Level V Standards
- Protection: Over Voltage/Short Circuit
- Packaged Unit Weight: 0.33 lbs
- Carton Quantity: 100 pcs

| | | | |
|-----------------|-----------------|---|---|
| ITEM NO. | S-48V0-0A5-UV30 | PART TITLE | Energy Efficient Vertical Blades 48 VDC / 0.5A Universal Input Power Supply |
| PART NO. | S6-480A5V |  CONDOR ELECTRONICS, INC. T: 408-745-7141 F: 408-745-0439 780 Montague Expy. Ste. 406 San Jose, CA 95131 USA sales@condorelectronics.net | |
| DATE | 07.15.2016 | | |
| APPROVAL | TN | | |
| UNIT | mm | | |
| REV | 0 | | |