


**Output Plug  
and Polarity are  
Dependent on  
Customer  
Requirements**

### General Specifications

- Input: 100~240Vac/ 47~63Hz
- Output: +48VDC/0~500mA Regulated
- DC Cord: 5 FT, 22 AWG
- Operating/Storage Temperature: 0°C ~+40°C/ -20°C~+80°C
- Operating/Storage Humidity: 20%~80%RH/ 10%~90%RH
- Approvals: UL/CUL/FCC/LPS/BSMI/WEEE/ROHS/VI
- Meets Energy Efficiency Level V Standards
- Protection: Over Voltage/Short Circuit
- Packaged Unit Weight: 0.33 lbs
- Carton Quantity: 100 pcs

<b>ITEM NO.</b>	S-48V0-0A5-UV30	<b>PART TITLE</b>	Energy Efficient Vertical Blades 48 VDC / 0.5A Universal Input Power Supply
<b>PART NO.</b>	S6-480A5V	 <b>CONDOR ELECTRONICS, INC.</b> T: 408-745-7141 F: 408-745-0439 990 San Antonio Road Palo Alto, CA 94303 USA <a href="mailto:sales@condorelectronics.net">sales@condorelectronics.net</a>	
<b>DATE</b>	07.15.2016		
<b>APPROVAL</b>	TN		
<b>UNIT</b>	mm		
<b>REV</b>	0		