



Output Plug and Polarity are Dependent on Customer Requirements

General Specifications

- Input: 100~240Vac/ 50~60Hz
- Output: +5VDC/0~1500mA Regulated
- DC Cord: 5FT, 20 AWG ROUND
- Operating/Storage Temperature: 0°C ~+40°C/ -20°C~+60°C
- Operating/Storage Humidity: 10%~90%RH/ 10%~95%RH
- Approvals: UL/CUL/FCC/CTICK/WEEE/CE/ROHS/ V
- Meets Energy Efficiency Level V Standards
- Protection: Over Voltage/Short Circuit
- Packaged Unit Weight: 0.26 lbs
- Carton Quantity: 140 pcs

<i>ITEM NO.</i>	S-5V0-1A5-U30	<i>PART TITLE</i>	Energy Efficient 5 VDC / 1.5A Universal Input Power Supply
<i>PART NO.</i>	SA-051A5P-US	 CONDOR ELECTRONICS, INC. T: 408-745-7141 F: 408-745-0439 990 San Antonio Road Palo Alto, CA 94303 USA sales@condorelectronics.net	
<i>DATE</i>	1.04.2016		
<i>APPROVAL</i>	CB		
<i>UNIT</i>	mm		
<i>REV</i>	0		